

# FIX 4.4

- Change History
- FIX components
  - Header
  - Trailer
  - Instrument
  - Parties
  - OrderQtyData
  - TradingSessions
  - NestedParties
- Transport level
  - Heartbeat (0)
  - TestRequest (1)
  - ResendRequest (2)
  - Reject (3)
  - SequenceReset (4)
  - Logout (5)
  - Logon (A)
- Application level messages
  - NewOrderSingle(D)
  - ExecutionReport(8)
  - OrderCancelRequest (F)
  - OrderCancelReplaceRequest (G)
  - OrderCancelReject(9)
  - SecurityListRequest(x)
  - SecurityList(y)
  - MarketDataRequest(V)
  - MarketDataRequestReject(Y)
  - MarketDataSnapshotFullRefresh(W)
  - MarketDataIncrementalRefresh(X)
  - SecurityStatusRequest(e)
  - SecurityStatus(f)

## Change History

Version	Data	Change details
---------	------	----------------

---

1.1	05.06.2021	NewOrderSingle added Execlnst 'y' for ignoring dynamic limits
-----	------------	---

## FIX components

### Header

Tag	Name	Type	Presence	Possible values	Description
8	BeginString	String	mandatory	FIX.4.4	Must be first
9	BodyLength	Length	mandatory		Must be second
35	MsgType	String	mandatory		Must be third
49	SenderCompID	String(32)	mandatory		
56	TargetCompID	String(32)	mandatory		
34	MsgSeqNum	SeqNum	mandatory		
50	SenderSubID	String(16)	optional		
43	PossDupFlag	Boolean	optional	'Y', 'N'	
97	PossResend	Boolean	optional	'Y', 'N'	
52	SendingTime	UTCTimestamp	mandatory		Example: 20140910-15:14:12
122	OrigSendingTime	UTCTimestamp	optional		

### Trailer

Tag	Name	Type	Presence	Possible values	Description
10	Checksum	String	mandatory		

### Instrument

Tag	Name	Type	Presence	Possible value	Description
55	Symbol	String(20)	mandatory		<p>Exchange symbol name. In case of multi-leg order, it can be filled with '[N/A]' in case of</p> <ul style="list-style-type: none"> <li>• multileg order. Can be also filled with combination of legs. E.g. 'BRH6-BRM9'</li> <li>• when SecurityID specified</li> </ul>

48	SecurityID	String	optional		Instead of Symbol(55) SecurityID can be specified as <ul style="list-style-type: none"> <li>• ISIN - instrument ISIN</li> <li>• instrument ID - internal XROAD instrument unique ID number. E.g. '1234589'</li> <li>• alias - internal XROAD unique (across all exchanges) instrument name. E.g. 'LKOH.TQBR', 'XBTUSD.BITMEX', etc</li> </ul>
22	SecurityIDSource	String	conditionally required	'4', '100', '101'	Required only if SecurityID specified <ul style="list-style-type: none"> <li>• '4' - SecurityID is an ISIN</li> <li>• '100' - SecurityID is a instrument unique number</li> <li>• '101' - SecurityID is a instrument alias</li> </ul>
207	SecurityExchange	Exchange	optional	e.g. 'XMIC', 'XLON'	Default value is 'XMIC'. Make sense only if instrument specified with Symbol(55) tag or SecurityID is an ISIN
11016	InstrumentCurrency	Currency	conditionally required	'RUB', 'USD', 'EUR', 'GBP', etc	Instrument currency. Required if instrument found by ISIN+SecurityExchange. Make sense for LSE, where instrument has different name with same ISIN and different currency

## Parties

	Tag	Name	Type	Presence	Possible values	Description
	453	NoPartyIDs	NumInGroup	conditionally required	1	Make sense only for FOND, CURR sections of MOEX
=>	448	PartyID	String	mandatory		Client code, sales initials, book
=>	447	PartyIDSource	char	mandatory	'D'	
=>	452	PartyRole	int	mandatory	3, 11, 38	3 - client code 11 - sales initials 38 - position account (book)

## OrderQtyData

Tag	Name	Type	Presence	Possible value	Description
38	OrderQty	Qty	mandatory		

## TradingSessions

	Tag	Name	Type	Presence	Possible values	Description
	386	NoTradingSessions	NumInGroup	conditionally required	1	Make sense only for MOEX exchange
=>	336	TradingSessionID	String	mandatory		Exchange trading session (e.g. TQBR, TQDB, etc)

## NestedParties

	Tag	Name	Type	Presence	Possible values	Description
--	-----	------	------	----------	-----------------	-------------

539	NoNestedPartyIDs	NumInGroup	conditionally required	1, 2	
=>	524	NestedPartyID	String	mandatory	Client code or account
=>	525	NestedPartyIDSource	char	mandatory	'D'
=>	538	NestedPartyRole	int	mandatory	3 - client code 24 - account

## Transport level

### Heartbeat (0)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = '0'
112	TestReqID	String	optional		
	<Trailer>		mandatory		

#### Example

8=FIX.4.4 9=58 35=0 34=3 49=qfixclient 52=20150430-10:58:53.098 56=xroad 10=054

### TestRequest (1)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = '1'
112	TestReqID	String	mandatory		
	<Trailer>		mandatory		

#### Example

8=FIX.4.4 9=73 35=1 49=xroad 56=qfixclient 34=4 52=20150430-10:59:03.098 112=XROAD\_TEST 10=032

### ResendRequest (2)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = '2'
7	BeginSeqNo	SeqNum	mandatory		
16	EndSeqNo	SeqNum	mandatory		

<Trailer>	mandatory		
-----------	-----------	--	--

Example

### Reject (3)

Tag	Name	Type	Presence	Possible value	Description
<Header>			mandatory		MsgType = '3'
45	RefSeqNum	SeqNum	mandatory		
16	RefTagID	int	optional		
372	RefMsgType	String	optional		
373	SessionRejectReason	int	optional		
58	Text	String	optional		
<Trailer>			mandatory		

Example

### SequenceReset (4)

Tag	Name	Type	Presence	Possible value	Description
<Header>			mandatory		MsgType = '4'
123	GapFillFlag	Boolean	optional	'Y', 'N'	
36	NewSeqNo	SeqNum	mandatory		
<Trailer>			mandatory		

Example

### Logout (5)

Tag	Name	Type	Presence	Possible value	Description
<Header>			mandatory		MsgType = '5'

58	Text	String	optional		
	<Trailer>		mandatory		

Example  
8=FIX.4.4 9=58 35=5 49=xroad 56=qfixclient 34=7 52=20150430-11:12:44.564 10=052

## Logon (A)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = 'A'
98	EncryptMethod	int	mandatory	0	
108	HeartBtInt	int	mandatory		
141	ResetSeqNumFlag	Boolean	optional	'Y', 'N'	Default is 'N'
553	Username	String	optional		
554	Password	String	optional		
	<Trailer>		mandatory		

Example  
8=FIX.4.4 9=68 35=A 34=1 49=quickfix 52=20150402-19:40:48.333 56=xroad 98=0 108=10 10=133

## Application level messages

### NewOrderSingle(D)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = 'D'
11	ClOrdID	String(32)	mandatory		
526	SecondaryClOrdID	String(32)	optional		user specific data. will be passed to exchange as is
	<Parties>		conditionally required		for FOND and CURR sections at MOEX exchange only
1	Account	String(16)	mandatory		
	<TradingSessions>		optional		Make sense only for MOEX FOND and CURR sections
	<Instrument>		mandatory		

54	Side	char	mandatory	'1' - Buy '2' - Sell	
60	TransactTime	UTCTimestamp	mandatory		
<OrderQtyData>			mandatory		
40	OrdType	char	mandatory	'1' - Market '2' - Limit	
44	Price	Price	conditionally required		If OrdType(40) tag != market
15	Currency	Currency	optional	'RUB', 'USD', 'EUR', 'GBP', etc	Price currency. Also used for instrument resolution by ISIN
21	HandlInst	char	optional	'1', '2', '3'	Instructions for order handling on Broker trading floor <ul style="list-style-type: none"> <li>'1' - Automated execution order, private, no Broker intervention</li> <li>'2' - Automated execution order, public, Broker intervention OK</li> <li>'3' - Manual order, best execution</li> </ul>
18	ExecInst	MultipleValueString	optional	'6', 'H', 'E', 'f', 'x', 'y', 'z', 't'	Execution instructions: <ul style="list-style-type: none"> <li>'6' - Participate don't initiate</li> <li>'H' - restate on system failed</li> <li>'E' - do not increase position</li> <li>'f' - close position. BITMEX specific</li> <li>'x' - cancel on cross. Crosser will not to try to re-execute order in this case</li> <li>'y' - ignore dynamic limits (for SPBEX)</li> <li>'z' - don't cross orders from MM</li> <li>'t' - transit orders</li> </ul>
529	OrderRestrictions	MultipleValueString	optional	'5'	<ul style="list-style-type: none"> <li>'5' - Acting as Market Maker or Specialist in the security</li> </ul>
58	Text	String(32)	optional		Free format text string
59	TimeInForce	char	mandatory	'0' - Day '1' - GTC '2' - At open '3' - IOC (Immediate Or Cancel) '4' - FOK (Fill Or Kill) '6' - GTD '7' - At close	
432	ExpireDate	LocalMktDate	conditionally required	'20150905'	Required only if TimeInForce(59) tag == 'GTD'
11000	AlgorithmType	char	conditionally required	'1' - iceberg '2' - TWAP '3' - VWAP '4' - POV '5' - Sniper '6' - Rake '7' - Scheduled	Required only if AlgorithmType(11000) tag == '7'(scheduled)
100	ExDestination	String	conditionally required	XMIC, XLON, XXRD, etc	execution market mic code. if 'XXRD' order will be executed at crosser
111	MaxFloor	Qty	conditionally required		Should be used for iceberg orders. Mandatory if AlgorithmType(11000) tag == '1'(iceberg), '4'(POV)
120	SettlCurrency	Currency	conditionally required	'USD', 'EUR'	hedge currency
121	ForexReq	boolean	optional	'Y' - hedge order	used to indicate that order should be hedged

168	EffectiveTime	UTCTimestamp	optional		used to scheduled orders
11002	AlgoStart	UTCTimeOnly	optional		TWAP/VWAP/POV UTC start time. If absent, current time is used
11003	AlgoStop	UTCTimeOnly	optional		TWAP/VWAP/POV UTC stop time. If absent, order will be traded till session end
11004	AlgoPeriod	Int	optional		POV period (in seconds). Default value is 3 seconds
11005	AlgoAggressionLevel	Int	optional		TWAP/VWAP/POV aggression level. Count of ticks price shift during Aggression time. Default is 0
11006	AlgoMidTime	Int	optional		TWAP/VWAP/POV mid price period in percent. Default is 30%
11007	AlgoAggressionTime	Int	optional		TWAP/VWAP/POV aggression price period in percent. Default is 30%
11008	AlgoPOVRate	float	conditionally required		POV participation rate (in percent). Mandatory if AlgorithmType(11000) tag == '4'(POV)
11009	AlgoVWAPPriceMove	float	conditionally required		VWAP maximum algo price deviation from market VWAP in percent
11013	AlgoWorkingInt	Int	conditionally required		RAKE working interval (in seconds)
11014	AlgoBookDepth	Int	optional		RAKE book depth. Default is 1
11015	AlgoLevelDistance	Int	optional		RAKE level distance. Default is 1
11017	AlgoMinQty	Int	optional		TWAP/VWAP/POV min qty in lots for micro orders
	<Trailer>		mandatory		

#### Example

8=FIX.4.4 9=178 35=D 34=2 49=quickfix 52=20150402-19:40:48.349 56=xroad 1=S01-00000F00 11=8/343504 38=1000 40=2 44=1834.1 54=1 55=LKOH 59=0 60=20150402-19:40:48 453=1 448=XXX 447=D 452=3 10=048

8=FIX.4.4 9=149 35=D 34=2 49=qfixclient 52=20150430-11:12:40.571 56=xroad 1=Z15 11=1/19975/0 15=RUB 38=1000 40=2 44=6800 54=2 55=OFZ6-6.15 59=0 60=20150430-11:12:40 10=187

8=FIX.4.4 9=211 35=8 34=2 49=xroad 52=20200211-08:41:46.995 56=client 6=0 11=1/18548/0 14=0 17=141 37=141 38=1 39=0 44=7000 54=1 55=XTUSD 59=0 60=20200211-08:41:46.804 150=0 151=1 198=2f576f92-232a-fcc4-e2d4-f6dd325e 207=XBMX 10=212

#### ExecutionReport(8)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = '8'
37	OrderID	String	mandatory		
11	ClOrdID	String(32)	mandatory		
41	OrigClOrdID	String(32)	optional		
198	SecondaryOrderID	String	optional		Can be used to provide order id used by exchange or executing system
527	SecondaryExecID	String	optional		Can be used to provide trade id used by exchange or executing system
17	ExecID	String	mandatory		



150	ExecType	char	mandatory	'0' - New '4' - Canceled '5' - Replaced '6' - Pending Cancel '8' - Rejected 'A' - Pending New 'C' - Expired 'E' - Pending Replace 'F' - Trade	
39	OrdStatus	char	mandatory	'0' - New '1' - Partially Filled '2' - Filled '4' - Canceled '6' - Pending Cancel '8' - Rejected 'A' - Pending New 'C' - Expired 'E' - Pending Replace	
103	OrdRejReason	int	optional		
	<TradingSessions>		optional		Make sense only for MOEX FOND and CURR sections
	<Instrument>		optional		
54	Side	char	mandatory	'1' - Buy '2' - Sell	
	<OrderQtyData>		mandatory		
44	Price	Price	conditionally required		If OrdType(40) tag != market
59	TimeInForce	char	mandatory		
432	ExpireDate	LocalMktDate	conditionally required		required only if TimeInForce(59) tag == 'GTD'
32	LastQty	Qty	optional		
31	LastPx	Price	optional		
30	LastMkt	Exchange	optional		Market of execution for last fill
151	LeavesQty	Qty	mandatory		
14	CumQty	Qty	mandatory		
6	AvgPx	Price	mandatory		Средневзвешенная цена
60	TransactTime	UTCTimestamp	optional		
58	Text	String	optional		
119	SettlCurrAmt	Qty	optional		Hedge amount
120	SettlCurrency	Currency	optional	'USD', 'EUR'	Hedge currency
155	SettlCurrFxRate	Price	optional		FX rate of hedge
11100	SettlCurrFxAvgRate	Price	optional		средневзвешенный курс хеджирования
11101	SettlCurrFxAvgPrice	Price	optional		средневзвешенная цена в валюте хеджирования

<Trailer>	mandatory		
-----------	-----------	--	--

Example  
8=FIX.4.4 9=150 35=8 49=xroad 56=qfixclient 34=2 52=20150430-11:12:40.623 37=1119 11=1/19975/0 17=1119 150=0 39=0 55=OFZ6-6.15 54=2 38=1000 44=6800 151=1000 14=0 6=0 10=013

### OrderCancelRequest (F)

Tag	Name	Type	Presence	Possible value	Description
<Header>			mandatory		MsgType = 'F'
11	ClOrdID	String(32)	mandatory		
41	OrigClOrdID	String(32)	mandatory		
<Instrument>			mandatory		
54	Side	char	mandatory	'1' - Buy '2' - Sell	
60	TransactTime	UTCTimestamp	mandatory		
<OrderQtyData>			mandatory		
<Trailer>			mandatory		

Example  
8=FIX.4.4 9=123 35=F 34=4 49=qfixclient 52=20150430-11:12:42.572 56=xroad 11=1/19975/2 41=1/19975/0 54=2 55=OFZ6-6.15 60=20150430-11:12:42 10=229

### OrderCancelReplaceRequest (G)

Tag	Name	Type	Presence	Possible value	Description
<Header>			mandatory		MsgType = 'G'
11	ClOrdID	String(32)	mandatory		
41	OrigClOrdID	String(32)	mandatory		
<Instrument>			mandatory		
54	Side	char	mandatory	'1' - Buy '2' - Sell	
60	TransactTime	UTCTimestamp	mandatory		
<OrderQtyData>			mandatory		
40	OrdType	char	mandatory	'1' - Market '2' - Limit	

44	Price	Price	mandatory		
111	MaxFloor	Price	optional		Make sense only for iceberg order
120	SettlCurrency	Currency	conditionally required	'USD', 'EUR'	hedge currency
121	ForexReq	boolean	optional	'Y' - hedge order	used for TWAP/VWAP/POV to indicate that order should be hedged
11002	AlgoStart	UTCTimeOnly	optional		For TWAP, VWAP, POV
11003	AlgoStop	UTCTimeOnly	optional		For TWAP, VWAP, POV
11004	AlgoPeriod	Int	optional		For POV
11005	AlgoAgressionLevel	Int	optional		For TWAP, VWAP, POV
11006	AlgoMidTime	Int	optional		For TWAP, VWAP, POV
11007	AlgoAgressionTime	Int	optional		For TWAP, VWAP, POV
11008	AlgoPOVRate	float	optional		For POV
11009	AlgoVWAPPriceMove	float	optional		For VWAP
11010	HedgeCurrency	Currency	optional		If 'XXX' currency is set, order will stop hedging if any
11013	AlgoWorkingInt	Int	optional		For RAKE
11014	AlgoBookDepth	Int	optional		For RAKE
11015	AlgoLevelDistance	Int	optional		For RAKE
11017	AlgoMinQty	Int	optional		TWAP/VWAP/POV min qty in lots for micro orders
	<Trailer>		mandatory		

Example

8=FIX.4.4 9=143 35=G 34=3 49=qfixclient 52=20150430-11:12:41.571 56=xroad 11=1/19975/1 38=400 40=2 41=1/19975/0 44=6800 54=2 55=OFZ6-6.15 60=20150430-11:12:41 10=104

OrderCancelReject(9)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = '9'
37	OrderID	String	mandatory		
11	ClOrdID	String(32)	mandatory		
41	OrigClOrdID	String(32)	mandatory		

39	OrdStatus	char	mandatory	'0' - New '1' - Partially Filled '2' - Filled '4' - Canceled '6' - Pending Cancel '8' - Rejected 'A' - Pending New 'C' - Expired 'E' - Pending Replace	
434	CxlRejResponseTo	char	mandatory	'1' - Order Cancel request '2' - Order Cancel/replace request	
102	CxlRejReason	int	optional	0 - Too late to cancel 1 - Unknown order 2 - Broker option 3 - Already in Pending state 6 - Duplicate CIOrdID 99 - Other	
58	Text	String	optional		
	<Trailer>		mandatory		

Example

8=FIX.4.4 9=109 35=9 49=xroad 56=qfixclient 34=6 52=20150430-11:12:42.663 37=1119 11=1/19975/2 41=1/19975/0 39=0 434=1 102=1 10=157

SecurityListRequest(x)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = 'x'
320	SecurityReqID	String	mandatory		
559	SecurityListRequestType	int	mandatory	'4' - all securities	
	<Trailer>		mandatory		

Example

8=FIX.4.4 9=76 35=x 34=14 49=qfix\_client 52=20151023-14:35:18.819 56=xroad\ 320=req\_1 559=4 10=207

SecurityList(y)

Tag	Name	Type	Presence	Possible value	Description
<Header>			mandatory		MsgType = 'y'
320	SecurityReqID	String	mandatory		
322	SecurityResponseID	String	mandatory		
560	SecurityRequestResult	int	mandatory	'0' - valid request '1' - invalid or unsupported request '2' - no instruments found	
393	TotNoRelatedSym	int	optional		
893	LastFragment	bool	optional	'Y' - last message 'N' - not last message	
146	NoRelatedSym	NumInGroup	conditionally required		
=>	<Instrument>		conditionally required		
=>	15	Currency	Currency	optional	
=>	561	RoundLot	Qty	optional	
=>	625	TradingSessionID	String	optional	
<Trailer>			mandatory		

Example

8=FIX.4.4 9=128 35=y 49=SENDER 56=TARGET 34=1 52=20151023-14:35:18.819 320=req\_1 322=1/5005/298 560=0 393=14 893=N 146=10 55=LKOH| 15=RUB 336=TQBR 55=Si-9.14 15=RUB 55=Si28500BU4 15=RUB 55=Si28000BI4 15=RUB 55=LKOH 15=RUB 336=EQRP 55=GAZR-9.14 15=RUB 55=GAZR-6.14 15=RUB 55=MFON 15=RUB 336=TQBR 55=SBER 15=RUB 336=TQBR 55=XYZ-6.15 15=RUB 10=256

## MarketDataRequest(V)

Tag	Name	Type	Presence	Possible value	Description
<Header>			mandatory		MsgType = 'V'
262	MDReqID	String	mandatory		
263	SubscriptionRequestType	char	mandatory	'0' - snapshot '1' - snapshot + updates '2' - unsubscribe	
264	MarketDepth	int	mandatory		
265	MDUpdateType	int	conditionally required	'0' - full refresh	
267	NoMDEntryTypes	NumInGroup	mandatory		
=>	269	MDEntryType	char	mandatory	'0' - bid '1' - offer '2' - trade

146	NoRelatedSym	NumInGroup	mandatory			
=>	<Instrument>		mandatory			
=>	<TradingSessions>		optional			
=>	854	QtyType	int	optional	'0', '1'	Type of quantity specified in a quantity field. Valid values: <ul style="list-style-type: none"> <li>'0' - Units (shares, par, currency)</li> <li>'1' - Contracts or lots (if used - ContractMultiplier can be specified)</li> </ul> If not specified, '1' is used
	<Trailer>		mandatory			

Example

8=FIX.4.4 9=134 35=V 34=6 49=qfix\_client 52=20151026-09:02:11.233 56=xroad 146=1 55=LKOH 386=1 336=TQBR 262=req\_1 263=1 264=0 267=3 269=0 269=1 269=2 10=224

### MarketDataRequestReject(Y)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = 'Y'
262	MDReqID	String	mandatory		
281	MDRequestRejReason	char	optional	'0' - unknown symbol '1' - duplicate MDReqID '5' - unsupported MarketDepth '6' - unsupported MDUpdateType '8' - unsupported MDEntryType	
58	Text	String	optional		
	<Trailer>		mandatory		

Example

8=FIX.4.4 9=71 35=Y 49=SENDER 56=TARGET 34=1 52=20151026-09:02:11.233 262=req\_1 281=8 10=128

### MarketDataSnapshotFullRefresh(W)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = 'W'
262	MDReqID	String	optional		
	<Instrument>		mandatory		
268	NoMDEntries	NumInGroup	mandatory		

=>	269	MDEntryType	char	mandatory	'0' - bid '1' - offer '2' - trade '4' - open '5' - close '7' - high '8' - low '9' - vwap 'B' - volume 'C' - open interest	
=>	270	MDEntryPx	Price	optional		
=>	15	Currency	Currency	optional		
=>	271	MDEntrySize	Qty	optional		
=>	273	MDEntryTime	UTCTimeOnly	optional		
=>	336	TradingSessionID	String	optional		
=>	290	MDEntryPositionNo	int	optional		
		<Trailer>		mandatory		

Example

8=FIX.4.4 9=116 35=W 49=SENDER 56=TARGET 34=2 52=20151026-09:02:11.233 55=LKOH 268=1 269=2 270=122 271=80 273=10:01:22.222 336=TQBR 10=128

### MarketDataIncrementalRefresh(X)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = 'X'
262	MDReqID	String	optional		
	<Instrument>		mandatory		
268	NoMDEntries	NumInGroup	mandatory		
=>	279	MDUpdateAction	mandatory	'0' - new '1' - change '2' - delete	
=>	269	MDEntryType	mandatory	'0' - bid '1' - offer '2' - trade '4' - open '5' - close '7' - high '8' - low '9' - vwap 'B' - volume 'C' - open interest	
=>	270	MDEntryPx	optional		

=>	15	Currency	Currency	optional		
=>	271	MDEntrySize	Qty	optional		
=>	273	MDEntryTime	UTCTimeOnly	optional		
=>	336	TradingSessionID	String	optional		
=>	290	MDEntryPositionNo	int	optional		
		<Trailer>		mandatory		

Example

8=FIX.4.4 9=116 35=X 49=SENDER 56=TARGET 34=4 52=20151026-09:02:11.233 262=REQ\_ID 268=1 279=0 269=1 55=LKOH 207=MISX 270=126.7 271=10 273=10:01:22.222 336=TQBR 10=128

### SecurityStatusRequest(e)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = 'e'
324	SecurityStatusReqID	String	mandatory		
	<Instrument>		mandatory		
=>	263	SubscriptionRequestType	char	mandatory	'0' - Snapshot '1' - Snapshot + Updates (Subscribe) '2' - Disable previous Snapshot + Update Request (Unsubscribe)
=>	<TradingSessions>		optional		
	<Trailer>		mandatory		

Example

8=FIX.4.4 9=134 35=e 34=2 49=SENDER 52=20151026-09:02:11.233 56=TARGET 324=req\_1 146=1 55=LKOH 386=1 336=TQBR 263=1 10=224

### SecurityStatus(f)

Tag	Name	Type	Presence	Possible value	Description
	<Header>		mandatory		MsgType = 'f'
324	SecurityStatusReqID	String	mandatory		
	<Instrument>		mandatory		



=>	263	SecurityTradingStatus	int	optional	2 - halt 17 - regular trading 18 - stopped 20 - unknown 21 - opening period 124 - closing period 125 - opening auction 126 - closing auction 127 - auction 128 - auction price trading 129 - auction closing	
=>	332	HighPx	Price	optional		
=>	333	LowPx	Price	optional		
=>	336	Text	String	optional		
=>	12000	FeedStatus	Int	optional	1 - Offline, 2 - Online	Market data feed status
		<Trailer>		mandatory		

**Example**

8=FIX.4.4 9=39 35=f 49=xroad 56=CLIENT 34=2 52=20151026-09:02:11.233 324=req\_1 55=LKOH 207=MISX 326=2 10=105